

## Shell Commercial Products

Shell commercial lubricants are designed to protect your equipment from the toughest conditions – heavy loads, extreme temperatures, mountainous terrain and continuous operation.

Shell ROTELLA® T engine oils have been specially formulated to protect against wear that results from abrasive soot, high-temperature operation and poor viscosity retention. ROTELLA® T exceeds the requirements for EGR engines



**ROTELLA® T Engine Oils**

<p><b>PRODUCTS</b></p> <ul style="list-style-type: none"> <li>• Multigrade Engine Oil</li> <li>• Single-Grade Engine Oil</li> <li>• Synthetic</li> <li>• Synthetic Blend</li> </ul>
<p><b>WEIGHTS</b></p> <ul style="list-style-type: none"> <li>• ROTELLA® T 15W-40, 10W-30</li> <li>• ROTELLA® T Synthetic 5W-40</li> <li>• ROTELLA® T Synthetic Blend 10W-30, 10W-40, 0W-30</li> <li>• ROTELLA® T Single Grades 10W, 20, 30, 40, 50</li> </ul>
<p><b>CONTAINERS</b></p> <ul style="list-style-type: none"> <li>• 1-Quart • 1-Gallon • 2.5 Gallon</li> <li>• 5-Gallon Pail • 55-Gallon Drums</li> <li>• Bulk</li> </ul>
<p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>• API CI-4/SL (Multigrade, Synthetic, Synthetic Blend)</li> <li>• CAT ECF-1, Mack EO-N Premium Plus (15W-40)</li> <li>• Cummins 20078 (15W-40, 10W-30)</li> <li>• Volvo VDS-3 (15W-40, 10W-40)</li> <li>• API CF-4, CF-2,CF/SL (30, 40, 50)</li> <li>• API CF/SL (10W, 20)</li> </ul>
<p><b>KEY FEATURES</b></p> <ul style="list-style-type: none"> <li>• Multigrade recommended for all EGR and non-EGR engines</li> <li>• Outstanding wear protection</li> <li>• Excellent soot handling properties</li> <li>• Outstanding high-temperature oxidation control</li> </ul>



**SPIRAX® Gear oils**

<p><b>PRODUCTS</b></p> <ul style="list-style-type: none"> <li>• SPIRAX® S • SPIRAX® EW • SPIRAX® LS • SPIRAX® HD</li> </ul>
<p><b>WEIGHTS</b></p> <ul style="list-style-type: none"> <li>• SPIRAX S 75W-90, 80W-140 • SPIRAX EW 75W-90, 80W-140</li> <li>• SPIRAX HD 80W-90, 85W-140 • SPIRAX LS 80W-90</li> </ul>
<p><b>CONTAINERS</b></p> <ul style="list-style-type: none"> <li>• Pail • Keg • Drum • Bulk</li> </ul>
<p><b>SPECIFICATIONS</b></p> <p>SPIRAX S &amp; SPIRAX EW</p> <ul style="list-style-type: none"> <li>• Eaton PS-163, PS-037</li> <li>• Dana SHAES 256, SHAES 254</li> <li>• Mack GO-J Plus (SPIRAX S 75W-90 only)</li> <li>• Mack GO-J (SPIRAX S 80W-140, SPIRAX EW 75W-90 and 80W-140)</li> <li>• ArvinMeritor O-76-N</li> <li>• MIL-PRF-2105E performance</li> <li>• API GL- 5</li> </ul> <p>SPIRAX HD</p> <ul style="list-style-type: none"> <li>• API GL-5, MT-1</li> <li>• Mack GO-J</li> <li>• ArvinMeritor O-76-A (85-140) &amp; O-76-D (80W-90)</li> <li>• MIL-PRF-2105E performance</li> </ul> <p>SPIRAX LS</p> <ul style="list-style-type: none"> <li>• API GL-5</li> </ul>
<p><b>KEY FEATURES</b></p> <ul style="list-style-type: none"> <li>• Heavy duty gear lubricants for on-and off-highway axles and transmissions in trucks, farm and construction equipment.</li> <li>• SPIRAX EW Gear Oils and SPIRAX S Gear Oils for Dana &amp; ArvinMeritor axles are approved extended warranty lubricants.</li> </ul>



**Transmission Lubricants**

<p><b>PRODUCTS</b></p> <ul style="list-style-type: none"> <li>• DENTAX® S</li> <li>• DENTAX®</li> </ul>
<p><b>WEIGHTS</b></p> <ul style="list-style-type: none"> <li>• DENTAX S SAE50</li> <li>• DENTAX SAE 80W-90, 140 &amp; 250</li> </ul>
<p><b>CONTAINERS</b></p> <ul style="list-style-type: none"> <li>• Pail • Keg • Drum • Bulk</li> </ul>
<p><b>SPECIFICATIONS</b></p> <p>DENTAX S</p> <ul style="list-style-type: none"> <li>• Eaton PS-164, PS-081</li> <li>• Mack TO-A Plus</li> <li>• ArvinMertor O-81</li> <li>• API MT-1</li> </ul> <p>DENTAX</p> <ul style="list-style-type: none"> <li>• API GL-1</li> </ul>
<p><b>KEY FEATURES</b></p> <ul style="list-style-type: none"> <li>• Heavy duty gear lubricants for on-and off-highway transmissions in trucks, farm and construction equipment where a non-EP API GL-1 lubricant is required.</li> <li>• DENTAX S is approved extended service synthetic lubricant for Eaton, Mack and ArvinMeritor Transmissions.</li> </ul>



### Power Transmission Lubricants

<p><b>PRODUCTS</b></p> <ul style="list-style-type: none"> <li>• DONAX® TC</li> <li>• DONAX® TD</li> <li>• DONAX® TD with Low Vis</li> </ul>
<p><b>WEIGHTS</b></p> <ul style="list-style-type: none"> <li>• DONTAX TC SAE 10W, 30, 50 &amp; 60</li> </ul>
<p><b>CONTAINERS</b></p> <ul style="list-style-type: none"> <li>• 2.5 gallon (DONAX TD)</li> <li>• Pail</li> <li>• Keg</li> <li>• Drum</li> <li>• Bulk</li> </ul>
<p><b>SPECIFICATIONS</b></p> <p>DONAX® TC</p> <ul style="list-style-type: none"> <li>• Caterpillar TO-4</li> <li>• Allison C-4 (SAE 10W &amp; 30)</li> </ul> <p>DONAX TD and Donax TD Low Vis</p> <ul style="list-style-type: none"> <li>• Power transmission, wet brake, hydraulic fluid recommended for use in farm and construction equipment made by most major manufacturers worldwide.</li> </ul>
<p><b>KEY FEATURES</b></p> <ul style="list-style-type: none"> <li>• Heavy duty power transmission fluids for on-and-off highway, farm and construction applications.</li> </ul>



### Diesel Fuel Additive

<p><b>PRODUCT</b></p> <ul style="list-style-type: none"> <li>• ROTELLA™ DFA</li> </ul>
<p><b>CONTAINERS</b></p> <ul style="list-style-type: none"> <li>• 32 oz • 96 oz • Drum</li> </ul>
<p><b>KEY FEATURES</b></p> <ul style="list-style-type: none"> <li>• All-season aftermarket product used in #2 diesel fuel to prevent fuel gelling and clean fuel injectors.</li> </ul>

### Anti-wear Hydraulic Oils

<p><b>PRODUCTS</b></p> <ul style="list-style-type: none"> <li>• Shell AW Hydraulic Oils</li> </ul>
<p><b>WEIGHTS</b></p> <ul style="list-style-type: none"> <li>• ISO 32, 46, 68</li> </ul>
<p><b>CONTAINERS</b></p> <ul style="list-style-type: none"> <li>• Pail • Keg • Drum • Bulk</li> </ul>
<p><b>KEY FEATURES</b></p> <ul style="list-style-type: none"> <li>• High quality anti-wear hydraulic oils for use in systems with vane, gear or piston pumps.</li> <li>• Excellent anti-wear properties, demulsibility and anti-foam performance.</li> </ul>



### Shell Greases

<p><b>PRODUCTS</b></p> <ul style="list-style-type: none"> <li>• RETINAX® LC #1 &amp; #2</li> <li>• RETINAX® TL #00</li> <li>• RETINAX® CMX #1 &amp; #2</li> <li>• RETINAX® SDX #2</li> <li>• RODINA® SDX #2</li> <li>• Albida SLC 220 #2</li> </ul>
<p><b>CONTAINERS</b></p> <ul style="list-style-type: none"> <li>• 14 oz cartridge</li> <li>• Pail</li> <li>• Keg</li> <li>• Drum</li> </ul>
<p><b>KEY FEATURES</b></p> <ul style="list-style-type: none"> <li>• Greases for use in heavy duty applications in trucks, buses, agricultural and construction equipment.</li> </ul>



### Extended Life Coolants

<p><b>PRODUCTS</b></p> <ul style="list-style-type: none"> <li>• Shell Dex-Cool®</li> <li>• ROTELLA® ELC Extended Life Coolant</li> </ul>
<p><b>CONCENTRATIONS</b></p> <ul style="list-style-type: none"> <li>• Concentrates • Pre-dilute 50/50</li> </ul>
<p><b>CONTAINERS</b></p> <ul style="list-style-type: none"> <li>• Gallons • Drums • Bulk</li> </ul>
<p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>• ASTM D 3306 &amp; ASTM D 4985 – Concentrates</li> <li>• ASTM D 6210</li> <li>• TMC RP 329, RP 338, RP 351</li> </ul>
<p><b>SHELL DEX-COOL - APPROVED OR MEETS PERFORMANCE SPECIFICATIONS -</b></p> <ul style="list-style-type: none"> <li>• GM 6277M • Renault • MB 325.3 (OF02, RL02)</li> <li>• Deutz 01999-99-2091 • WSS M97B44D (OF02)</li> <li>• Kobelco • DAF DW03245403 • Leyland DW03245403 • Man 324 Type SNF</li> </ul>
<p><b>ROTELLA ELC EXTENDED LIFE COOLANTS - APPROVED OR MEETS PERFORMANCE SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>• CAT EC-1 • Navistar B1 Type 3</li> <li>• Detroit Diesel 7SE298 – • Cummins ES 14603</li> <li>• Mack Extended Life Specification (SB-232-014) or 014 GS 17009 • Volvo TSI 184001</li> </ul>
<p><b>KEY FEATURES</b></p> <ul style="list-style-type: none"> <li>• Lowest overall cost of operation over 600,000 miles of usage. Improves heat transfer over conventional coolants. Improves hardware life.</li> </ul>

### Conventional Coolants

<p><b>PRODUCTS</b></p> <ul style="list-style-type: none"> <li>• Shellzone® (conventional)</li> <li>• Shell Diesel Ready (fully formulated)</li> </ul>
<p><b>CONCENTRATIONS</b></p> <ul style="list-style-type: none"> <li>• Concentrates • Pre-dilute 50/50</li> </ul>
<p><b>CONTAINERS</b></p> <ul style="list-style-type: none"> <li>• Gallons • Drums • Bulk</li> </ul>
<p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>• Shellzone Antifreeze/Coolant - ASTM D 3306 &amp; RP 302A</li> <li>• Shell Diesel Ready: ASTM D 6210, TMC RP 302B &amp; TMC RP 329</li> </ul>
<p><b>SHELLZONE – APPROVED OR MEETS PERFORMANCE SPECIFICATIONS OF:</b></p> <ul style="list-style-type: none"> <li>• Mack • Cummins 90T8-4 • JI Case JIC501 • John Deere H24B1 and H24C1</li> <li>• Freightliner • Mack • Paccar</li> </ul>
<p><b>SHELL DIESEL READY – APPROVED OR MEETS PERFORMANCE SPECIFICATIONS OF:</b></p> <ul style="list-style-type: none"> <li>• Mack • Cummins • Paccar • Caterpillar</li> <li>• Volvo • Waukesha 4-1947D • JI Case JIC501</li> </ul>
<p><b>KEY FEATURES</b></p> <ul style="list-style-type: none"> <li>• Conventional coolants for cost sensitive customer not concerned with extended service intervals. Requires the use of supplemental coolant additives.</li> </ul>